


**PUSH-OUT CONTAINER**

**Patent number:** JP11263366  
**Publication date:** 1999-09-28  
**Inventor:** YONETANI YOSHINOBU; KAWAHARA AKIYOSHI;  
 NAKAGAWA YASUHIRO; HOTTA TAJI  
**Applicant:** YAMAHATSU SANGYO KAISHA; TAISEI KAKO CO  
**Classification:**  
 - international: **A45D19/00; A45D19/02; B65D47/06; B65D47/44;  
 A45D19/00; B65D47/00; B65D47/06; (IPC1-7):  
 B65D47/44; A45D19/00; A45D19/02; B65D47/06**  
 - european:  
**Application number:** JP19980066534 19980317  
**Priority number(s):** JP19980066534 19980317

Report a data error here

**Abstract of JP11263366**

**PROBLEM TO BE SOLVED:** To improve simplicity and rapidness at the time of application in a container for receiving a first substance to be mixed with a different substance for application. **SOLUTION:** The push-out container includes a body 1 for receiving a first substance and allowing the first substance to be pushed out via an opening 1a and a lid member 10 attached to the body 1 to surround the opening 1a. A check valve 20 for preventing fluid from flowing from the outside into the container and allowing the first substance to flow from the inside of the container to the outside and an application member 30 which can container a second substance from the outside for applying the first substance pushed out from the inside of the container while being mixed with the second substance are provided in the lid member 10.

Data supplied from the **esp@cenet** database - Worldwide